



M15-22A-K-PP

## 1.000 - 3.000 l/h Cartridges

### Typical applications

Plating and process industry

### Features

- Magnetic drive pump
- Filter chamber with welded bottom (no seal)
- One or two filter chambers (parallel or serial)
- String wound, spunbonded, pleated or carbon cartridges
- All PP or PVDF construction
- Max. temperature PP 80°C / PVDF 100°C
- Unions for rigid piping (PP, PVDF or CPVC sockets)
- Standard with 3 phase motor, thermal overload switch, lead without plug, air release and drain valve

### Options

- Hose connection
- Pressure gauge
- Single phase motor
- Switch with auxiliary contact
- Single open end cartridges
- PVDF
- Viton



M10-11A-K-PP

## Filter Systems series 1

 [www.hendor.com](http://www.hendor.com)

Pump	l/h	kW*	Union (d/DN) In Out	Hose In Out	Type	Chamber	Medium	Material
Magnetic drive	1000	0,18			M10	11A	K	PP-EPDM PVDF-Viton
	2000	0,18	32/25	25/20	M11	12A		
	3000	0,18			M15	21A 22A		
Selection:					M15	22A	K	PP

\* For 3-phase motors < 220V the indicated motor will be one size bigger.

K = cartridges  
Qty x L  
11A-K = 1 x 10"  
12A-K = 1 x 20"

Parallel filtration  
Qty x L  
21A-K = 2 x 10"  
22A-K = 2 x 20"

Serial filtration  
Qty x L  
21AS-K = 2 x 10"  
22AS-K = 2 x 20"