



MX260-232A-K-PP

18.000 - 36.000 l/h Cartridges

Typical applications
Plating and process industry

Features

- Service friendly, ideal cleaning access height
- Magnetic drive or mechanical seal pump
- Filter chamber with welded bottom (no seal)
- DOE cartridges
- All PP construction, max. temperature PP 80°C
- Unions for rigid piping (PP, PVDF or CPVC sockets)
- Standard with 3 phase motor, thermal overload switch, lead without plug, pressure gauge, air release and drain valve

Options


- Hose connection
- Dry run protection
- Contact manometer
- By pass with flowmeter
- Single open end cartridges
- Viton

Filter Systems series 23

 www.hendor.com

Pump	l/h	kW	Union (d/DN)		Hose		Type	Chamber	Medium	Material
			In	Out	In	Out				
Magnetic drive	24000	1,5	50/40	50/40	2"	2"	MX260	232A	K	PP-EPDM
	30000	2,2	63/50	63/50	2½"	2½"	MX350			
	36000	3					MX410			
Mechanical seal	18000	1,5	50/40	50/40	2"	2"	S150	232A	K	PP-EPDM
	22000	2,2	63/50	63/50	2½"	2½"	S220			
	30000	3					S300			

Selection: MX260 232A K PP

K = cartridges
 Qty x L
 232A-K = 23 x 20"